



FLECK[®] 2750 1-INCH CONTROL VALVE

IDEAL FOR RESIDENTIAL OR COMMERCIAL FILTER AND SOFTENER APPLICATIONS



FEATURES/BENEFITS

- Lead-free brass valve body for superior strength and durability
- Continuous service flow rate of 26 GPM with a backwash of 25 GPM
- Backwash capability accommodates softener tanks up to 30" and filter up to 21" in diameter
- Fully adjustable 3- or 5-cycle control for efficient and reliable water treatment system

- Time-tested, hydraulically-balanced piston for service and regeneration
- Rugged-built electromechanical timer designed with heavy duty 3/8" wide plastic gears

OPTIONS

- Filter or softener control valves
- No hard water bypass piston
- Brine cam auxiliary switch
- Electromechanical timer auxiliary switch
- Hot water
- Electromechanical 7- or 12-day time clock, meter delayed, or meter immediate regeneration
- Manual lever operations

NXT- Network controller uses on-board communication capabilities to link multiple valves (via off-the-shelf CAT3, CAT5, or better cables) for system types 4,5,6,7,9, and 14.

SXT- Large LCD display and user-selectable time clock or metered function; usable for filtration and softener systems.

XT- Offers a two-line, 16 character LCD backlit display for easy entering of master and user programming as well as view of diagnostics.

Electromechanical Timer- Simple to adjust and easy to service with quick access to all internal components.



TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 61 Section 8 Material Safety Only.



TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 372 for Lead Free Compliance.



UL recognized to 979



Restriction of Hazardous Substance Compliant

VALVE SPECIFICATIONS

| | |
|----------------|------------------|
| Valve Material | Lead-free brass* |
| Inlet/Outlet | 1" NPTM/BSPM |
| Cycles | 3 or 5 |

FLOW RATES (50 PSI INLET) – VALVE ALONE

| | |
|------------------------------|-----------------------------------|
| Continuous 15 psi drop | 26 GPM (5.9 m ³ /h) |
| Peak 25 psi drop | 33 GPM (7.5 m ³ /h) |
| Cv flow at 1 psi drop | 6.8 |
| Max. Backwash 25 psi drop | 25 GPM (5.7 m ³ /h) |

REGENERATION

| | |
|--------------------|--------------------------|
| Downflow/Upflow | Downflow only |
| Adjustable Cycles | Yes |
| Time Available | |
| Electromechanical: | 0 - 164 min/regeneration |
| SXT: | 0 - 199 min/cycle |
| NXT: | 0 - 240 min/cycle |
| XT: | 0 - 240 min/cycle |

METER INFORMATION

| | |
|----------------------|---|
| Meter Accuracy | |
| 3/4" Paddle: | 0.25 - 15 GPM ± 5% (0.06 - 3 m ³ /h) |
| 1" Paddle: | 0.7 - 40 GPM ± 5% (0.16 - 9 m ³ /h) |
| 1" Turbine: | 2 - 40 GPM +5/-8% (0.45 - 9 m ³ /h) |
| Meter Capacity Range | |
| 3/4" Standard: | 125 - 2,125 gal (0.5 - 8 m ³) |
| 3/4" Extended: | 625 - 10,625 gal (2.5 - 40 m ³) |
| 1" Standard: | 310 - 5,270 gal (1.2 - 20 m ³) |
| 1" Extended: | 1,550 - 26,350 gal (6 - 100 m ³) |
| SXT: | 1 - 999,900 gal (0 - 3,785 m ³) |
| NXT: | 1 - 9,900,000 gal (0 - 37,476 m ³) |
| XT: | 1,000 - 9,900,000 gal (3.8 - 37,476 m ³) |

DIMENSIONS

| | |
|----------------------------|------------------------|
| Distributor Pilot | 1.05" O.D. (26.7 mm) |
| Drain Line | 3/4" NPTM |
| Brine Valve | |
| 1600 or 1650: | 3/8" |
| 1700 or 1710: | 1/2" |
| Injector System | 1600 or 1700 |
| Mounting Base | 2.5" - 8 NPSM |
| Height from Top of Tank | 6.5" (165 mm) |
| Riser Tube Diameter | 3/4" (19 mm) |
| Riser Height | Flush with top of tank |

TYPICAL APPLICATIONS

| | |
|----------------|--|
| Water Softener | 10 - 30" diameter |
| Filters | 10 - 21" diameter based on 10 GPM/ft ² |

ADDITIONAL INFORMATION

| | |
|---------------------------------------|---------------------------------|
| Electrical Rating | 24/110/220V 50/60 Hz |
| Estimated Shipping Weight | |
| Time Clock: | 13 lbs |
| Metered Valve: | 26 lbs |
| Pressure | |
| Hydrostatic: | 300 psi (20 bar) |
| Working: | 20 - 125 psi (1.4 - 8.5 bar) |
| Temperature | |
| Cold Water Valve: | 34 - 110°F (1 - 43°C) |
| Hot Water Valve: | 34 - 180°F (1 - 82°C) |
| Filter, Time Clock, 1600 Brine System | |
| Hot Water Valve: | 34 - 150°F (1 - 66°C) |
| Meter, 1700 Brine System | |

*As defined in the U.S. EPA Safe Drinking Water Act; the product also meets California Proposition 65 Standards for lead-free brass.



All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

40737 REV E JL14 © 2013 Pentair Residential Filtration, LLC. All Rights Reserved.