

Multi-Cartridges Stainless Steel Filter Housings

Capacity: 6 to 3,000 GPM

SSC

SERIES

SSC-I Series (Industrial)

Model #	Cartridges Requirement	Pipe Size (Flange)	Max. Flow Rate (GPM)	Drain Size (NPT)	Dimensions (W"xH")	Shipping Weight (lbs)
SSC-24	(6) of 40"	3"	144	1/2"	14.5x57	86
SSC-28	(7) of 40"	3"	168	1/2"	14.5x57	66
SSC-36	(9) of 40"	3"	216	1/2"	16.5x60	92
SSC-48	(12) of 40"	4"	288	1/2"	20.5x60	100
SSC-66	(22) of 30"	4"	396	1/2"	20.5x53	165
SSC-88	(22) of 40"	6"	528	1/2"	22.5x63	175
SSC-108	(27) of 40"	6"	660	1/2"	24.5x60	205
SSC-144	(36) of 40"	6"	720	1/2"	31.5x83.5	225
SSC-168	(42) of 40"	6"	1,008	1/2"	31.5x83.5	250
SSC-220	(55) of 40"	8"	1,320	1/2"	31.5x83.5	275
SSC-244	(61) of 40"	8"	1,464	1/2"	31.5x83.5	300
SSC-292	(73) of 40"	8"	1,752	1/2"	38x83.5	310
SSC-390	(98) of 40"	10"	2,340	1/2"	38x83.5	325
SSC-480	(120) of 40"	10"	2,880	1/2"	40x83.5	335
SSC-600	(150) of 40"	10"	3,000	1/2"	44x83.5	345

SSC-C Series (Commercial)

Model #	Cartridges Requirement	Pipe Size (MNPT)	Max. Flow Rate (GPM)	Drain Size (NPT)	Dimensions (W"xH")	Shipping Weight (lbs)
SSC-4	(4) of 10"	2"	24	1/2"	10.5x21	25
SSC-5	(5) of 10"	2"	30	1/2"	10.5x21	27
SSC-8	(4) of 20"	2"	48	1/2"	10.5x28	31
SSC-10	(5) of 20"	2"	60	1/2"	10.5x31.5	33
SSC-12	(4) of 30"	2"	72	1/2"	10.5x41	38
SSC-14	(7) of 20"	2"	84	1/2"	14x31.5	44
SSC-15	(5) of 30"	2"	90	1/2"	10.5x41	38
SSC-16	(4) of 40"	2"	96	1/2"	10.5x51.5	45
SSC-20	(5) of 40"	2"	120	1/2"	10.5x51.5	45
SSC-21	(7) of 30"	2"	126	1/2"	14.5x41.5	55

SSC-R Series (Residential)

Model #	Cartridges Requirement	Pipe Size (FNPT)	Max. Flow Rate (GPM)	Drain Size	Dimensions (W"xH")	Shipping Weight (lbs)
SSC-1	(1) of 10"	3/4"-1"	6	1/4"	3.5x14	6
SSC-2	(1) of 20"	3/4"-1"	12	1/4"	3.5x24	8
SSC-3	(1) of 30"	3/4"-1"	18	1/4"	3.5x33	11

Pure Aqua also supplies: Custom Engineered Solutions, Multimedia Pretreatment, Activated Carbon Pretreatment, Chemical Dosing Systems, Ultraviolet (UV) Sterilizers and Ozonation Systems.