

Stainless Steel Pressure Gauges

2.5" Dial, 30 to 1,500 PSI



Pure Aqua's pressure gauges are constructed with stainless steel casings and are glycerin filled. The pressure gauges are graduated to indicate psi/bar and are designed to measure up to 1,500 psi/100 bar. With two different mounting styles, users are able to choose between panel mount and side mount.



Part Number	Pressure Rating (psi)	Dial Size (in)	Glycerin Filled	Mount	Clamp	Process Connection
PG-30-P-316	0-30	2.5	Yes	Back	Yes	1/4" MNPT
PG-60-P-316	0-60	2.5	Yes	Back	Yes	1/4" MNPT
PG-100-P-316	0-100	2.5	Yes	Back	Yes	1/4" MNPT
PG-150-P-316	0-150	2.5	Yes	Back	Yes	1/4" MNPT
PG-350-P-316	0-350	2.5	Yes	Back	Yes	1/4" MNPT
PG-600-P-316	0-600	2.5	Yes	Back	Yes	1/4" MNPT
PG-1500-P-316	0-1500	2.5	Yes	Back	Yes	1/4" MNPT
PG-100-S-316	0-100	2.5	Yes	Bottom	No	1/4" MNPT
PG-350-S-316	0-350	2.5	Yes	Bottom	No	1/4" MNPT
PG-1500-S-316	0-1500	2.5	Yes	Bottom	No	1/4" MNPT

Standard Features

- 304 stainless steel case liquid filled
- SS 316 wetted part
- Patented movement with polyester segment
- Pressure ranges from 0 to 1,500 psi
- Pure Aqua indication, a unique safety feature
- Individually boxed

Applications

- Reverse osmosis
- Nanofiltration
- Ultrafiltration
- Electrodeionization
- Cartridge filters
- Water softeners
- Deionizers
- Media filters

Materials of Construction

Component	Material
Casing	304 stainless steel
Wetted Parts	316 stainless steel
Liquid Filled	Glycerin
Internal Screws	Stainless steel
Scale	Dual (psi/bar)
Window	Polycarbonate
Dial	Black/blue figures on white background, aluminum

To order Pure Aqua's pressure gauges (sample coding shown) Select:



1. Liquid filled pressure gauge, 2.5" dial size — PG
2. Pressure range — 100
3. 1/4" NPT connection, S for side, P for panel mount — P
4. SS 304 case material/SS 316 wetted part — 316