

Stainless Steel Solenoid Valves

1/2", 3/4", 1", 1-1/2" and 2" NPT

SV

SERIES

Pure Aqua's solenoid valves are constructed of high quality 304 or 316 stainless steel to insure a lifetime of use under even the most demanding conditions. Corrosion resistant, high flow capacity and easy to install, making Pure Aqua's solenoid valves a must have for controlling flow in your water treatment systems. Available for commercial and industrial use in 1/2", 3/4", 1", 1-1/2" and 2" NPT sizes with a pressure rating up to 145 psi (10 bar).



Standard Features

- 💧 Compact design
- 💧 304 or 316 stainless steel construction
- 💧 EPDM Diaphragm
- 💧 Corrosion resistant
- 💧 Pressure rating up to 145 psi (10 bar)
- 💧 DIN electrical connection
- 💧 High flow capacity

Applications

- 💧 Reverse osmosis
- 💧 Nanofiltration
- 💧 Ultrafiltration
- 💧 Electrodeionization
- 💧 Water filtration
- 💧 Commercial & Industrial

Part #		Connection (FNPT)	Electrical	Material
304 SS	316 SS			
SV-1/2-304SS-110	SV-1/2-316SS-110	1/2"	110V, 50-60Hz	304 SS/316 SS
SV-1/2-304SS-220	SV-1/2-316SS-220	1/2"	220V, 50-60Hz	304 SS/316 SS
SV-3/4-304SS-110	SV-3/4-316SS-110	3/4"	110V, 50-60Hz	304 SS/316 SS
SV-3/4-304SS-220	SV-3/4-316SS-220	3/4"	220V, 50-60Hz	304 SS/316 SS
SV-1-304SS-110	SV-1-316SS-110	1"	110V, 50-60Hz	304 SS/316 SS
SV-1-304SS-220	SV-1-316SS-220	1"	220V, 50-60Hz	304 SS/316 SS
SV-1-1/2-304SS-110	SV-1-1/2-316SS-110	1-1/2"	110V, 50-60Hz	304 SS/316 SS
SV-1-1/2-304SS-220	SV-1-1/2-316SS-220	1-1/2"	220V, 50-60Hz	304 SS/316 SS
SV-2-304SS-110	SV-2-316SS-110	2"	110V, 50-60Hz	304 SS/316 SS
SV-2-304SS-220	SV-2-316SS-220	2"	220V, 50-60Hz	304 SS/316 SS

*Pure Aqua's solenoid valves are 100% pressure tested, individually packaged and in stock ready for shipment.